

## ■ Portable folding camping kit



FDS-40W-12

### Specification:

Module type	<b>FDS-40W-12</b>
Nominal peak power(Wp)	40W
Nominal voltage(Vmp)	17.5V
Nominal current(Imp)	2.29A
Open-circuit voltage(Voc)	22V
Short-circuit current(Isc)	2.54A
Operating temperature	-20°C to +60°C
Maximum system voltage	600V DC
Weight	6.6kg
Dimension	505×370×75 mm

Packing: 555 × 250 × 425 mm

2pcs/ctn

G.W.: 16kg/ctn N.W.: 13.2kg/ctn

Qty/20' FCL: 704pcs

Qty/40' FCL: 1408pcs



FDS-60W-12

### Specification:

Module type	<b>FDS-60W-12</b>
Nominal peak power(Wp)	60W
Nominal voltage(Vmp)	17.5V
Nominal current(Imp)	3.43A
Open-circuit voltage(Voc)	22V
Short-circuit current(Isc)	3.81A
Operating temperature	-20°C to +60°C
Maximum system voltage	600V DC
Weight	8.5kg
Dimension	505×520×75 mm

Packing: 555 × 250 × 575 mm

2pcs/ctn

G.W.: 20.2kg/ctn N.W.: 17kg/ctn

Qty/20' FCL: 528pcs

Qty/40' FCL: 1056pcs

