

Product Name:MK-500PS

Input volt: 12V/24V/48VDC

Output volt: 110V/220VAC

Output waveform : pure sine wave

Output power:500W



A	B	C	D	E	F
USA	AUSTRALIA	UNIVERSAL	U.K	FRANCE	GERMANY

Function details

Model	MK-500PS-121	MK-500PS-241	MK-500PS-481	MK-500PS-122	MK-500PS-242	MK-500PS-482
AC output voltage	500W	500W	500W	500W	500W	500W
Max. Contins Power	1000W	1000W	1000W	1000W	1000W	1000W
DC input voltage	12V	24V	48V	12V	24V	48V
AC output voltage	110VAC			220VAC		
No-load current	0.6A	0.3A	0.15A	0.6A	0.3A	0.15A
AC output frequency	60HZ			50HZ		
AC output waveform	Pure Sine Wave					
Waveform Distortion	THD 2%(Linear load)					
Efficiency	>85%	>88%	>90%	>85%	>88%	>90%
DC input voltage range	10.5-15V	21-30V	42-60V	10.5-15V	21-30V	42-60V
Low Voltage Alarm	10.5-15V	21-30V	42-60V	10.5-15V	21-30V	42-60V
Low Voltage Shutdown	10.5+/-0.5V	21+/-1V	42+/-2V	10.5+/-0.5V	21+/-1V	42+/-2V
Over Voltage Protection	15.5+/-0.5V	31+/-1V	62+/-2V	15.5+/-0.5V	31+/-1V	62+/-2V
Low Voltage Recovery	12+/-0.5V	24+/-1V	48+/-2V	12+/-0.5V	24+/-1V	48+/-2V
Over Voltage Recovery	14.8V	29.5V	59V	14.8V	29.5V	59V
Protective Function	Low/Over voltage		LED Red light, automatic recovery			
	Over load		LED Red light, automatic recovery			
	Over temperature		LED Red light, automatic recovery			
	Short circuit		LED Red light, automatic recovery			
	Input reverse connection		Fuse Burn-out			
Working Temp.	0-40C					
Storage Tem. Humidity	(-30)-70C					
Dimension	250*169*61.5mm					
Weight	1.8KG					