

HPT4000 Series


Intelligent MPPT Hybrid Inverter



Features

- Professional solution for Off-Grid solar system
- Auto switch 5 FUN:
DC to AC , AC bypass, AC charger, solar charger and UPS
- MPPT Solar Charger. Max solar panel power:3120W
- DIP Switches : Low Battery, AC Input Range , Power Saver, O/P Frequency, Solar/Utility AC Priority
- Efficiency up 3~5% than SPT, Idle consumption down 30~50%
- Output AVR: stabilized AC voltage RMS(optional)
- Start Auto restart while AC is recovering (optional)
- Dry contact: alarm signal to start AC backup(optional)
- RTS: Measure battery temp. to make temp. compensation (optional)
- Remote control RJ45/RS232 :PTM-9 and PTM-12(optional)
- Pure sine wave output, for various load
- Input : Utility AC or Generator etc
- Solar power mode and Grid power mode, can be free choose
- Advanced microprocessor control design
- UVP/OVP/OSP/OLP/OTP protection

Solar charger: MPPT VS PWM



Remark : *2 FOR 24VDC, *4 FOR 48VDC

HPT4000 Series

Intelligent MPPT Hybrid Inverter

Item	Models	HPT4000-1485	HPT4000-1486	HPT4000-1489	HPT4000-2485	HPT4000-2486	HPT4000-2489
AC OUT-PUT	Output Power	4000W					
	Surge Power	12000W(≤20S)					
	Output Frequency	50/60Hz ±0.5%					
	Output Waveform	True sine wave (THD<3%)					
	P·F Allowed	COSθ-90°~COSθ+90°					
	Efficiency	90%					
DC IN-PUT	Input Voltage	48VDC					
	Voltage Range	20.0~31.0VDC,*2 for 48VDC/21.0~32.0VDC,*2 for 48VDC					
	Fault Indication	LED Red and Buzzer Alarm					
	Remote Control	RS-232/RJ11(Optional)					
AC Charger	AC Range	184-253VAC (AVR:176-276VAC) /154-253VAC (AVR:150-276VAC) 100-135VAC (AVR:92-144VAC) /90-135VAC (AVR:78-144VAC)					
	AVR Output AC	120VAC±10%			230VAC±10%		
	Output Voltage	Fast(14.0~15.1V), Float(13.3-13.8V).(*2 for 24vdc,*4 for 48vdc)					
	Over charge Protection	15.7V for 12V(*2 for 24vdc,*4 for 48vdc)					
	Charge Current	30A					
Solar charger PWM	solar panel Max	2440W		2880W		4800W	
	Rated Voltage	48VDC					
	Rated charge current	50A		60A		100A	
	DC Load Current	15A (MAX)					
	Input PV Voltage	16-55VDC/60~96VDC					
MPPT Solar Charger (optional)	solar panel Max	2340W		3120W		4680W	
	Rated Voltage	48VDC					
	Rated charge current	45A		60A		90A	
	DC Load Current	15A (MAX)					
	Input PV Voltage	150VDC(MAX)					
	Temp. compensation	-13.2mv/℃(*2 for 24vdc,*4 for 48vdc)					
Bypass	Transfer Time	<8 ms					
	Input Volt. waveform	Utility AC or Generator (Sine wave)					
	Max bypass current	80A/40A					
Others	Working Humidity	20-90%RH					
	Safety and EMI	UL458			LVD (EN60950)		
	Working temp.	-20~50℃					
	Storage Temp	-30~70℃					
	Cooling	Temperature controlled cooling fan					
	Size (mm)	488*415*200					
	Weight (kg)	43/48					