


**Product Name:MK-1000M**

Input volt: 12V/24V/48VDC

Output volt: 110V/220VAC

Output waveform :Modified sine wave

Output power: 1000W

<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>
USA	AUSTRALIA	UNIVERSAL	U.K	FRANCE	GERMANY

**Function**

Model	MK-1000M-121	MK-1000M-241	MK-1000M-481	MK-1000M-122	MK-1000M-242	MK-1000M-482
Rated power	1000W	1000W	1000W	1000W	1000W	1000W
Peak power	2000W	2000W	2000W	2000W	2000W	2000W
DC input voltage	12V	24V	48V	12V	24V	48V
AC output voltage	110VAC			220VAC		
No-load current	0.5A	0.25A	0.13A	0.5A	0.25A	0.13A
AC output frequency	60HZ			50HZ		
AC output waveform	Modified Sine Wave					
Efficiency	>85%	>88%	>90%	>85%	>88%	>90%
DC input voltage range	10.5-15V	21-30V	42-60V	10.5-15V	21-30V	42-60V
Low Voltage Alarm	10.5±0.5V	21±1V	42±2V	10.5±0.5V	21±1V	42±2V
Low Voltage Shutdown	10±0.5V	20±1V	40±2V	10±0.5V	20±1V	40±2V
Over Voltage Protection	15.5±0.5V	31±1V	62±2V	15.5±0.5V	31±1V	62±2V
Low Voltage Recovery	12±0.5V	24±1V	48±2V	12±0.5V	24±1V	48±2V
Over Voltage Recovery	14.8V	29.5V	59V	14.8V	29.5V	59V
Protective Function	Low/Over voltage		LED Red light, automatic recovery			
	Over load		LED Red light, automatic recovery			
	Over temperature		LED Red light, automatic recovery			
	Short circuit		LED Red light, automatic recovery			
	Input reverse connection		Fuse Burn-out			
Working Temp.	0℃-40℃					
Storage Temp. Humidity	-30℃-70℃					
Dimension	265*123*70mm					
Weight	2.2KG					